



UC520

IP Office for SOHO



UC520 is specially designed as IP Office for SOHOs (Small Office and Home Offices). The new solution offers not only a Wi-Fi router supporting VPN Client/Server, external ADSL, ... but also a fully featured IP PBX that can host up to 10 extensions with 2 analog ports connected (PSTN line (FXO)/ analog phone (FXS)); and supports Call Forward, Blind/Attendant Transfer and so on. Moreover, LTE is supported for mobile network connection.

UC520 is configured and managed through a single web GUI which significantly reduces the time and effort required to install the product. This simplified management and reduction in hardware costs through merging two products into one makes the UC520 an amazing and cost effective solution for SOHOs.



System Specifications

IP PBX Features

Extensions

10 Extensions
Batch-Add Extensions
UDP/TCP Transport
SIP/IAX/FXO Trunks

Outbound Routes

DialPlan
IVR

Inbound Controls

Analog Port DID
Number DID
DOD
IVR
IVR Prompts
Ring Group
Blacklist
Time Based Rules

Codect

Audio: G.722/G.711-Ulaw/G.711-Alaw/
G.726/G.729/GSM/SPEEX

DTMF

RFC2833
SIP info
Inband

Call Features

Caller ID
Call Group
Call Hold
Call Waiting
Call Transfer
Call Forward (Always/Busy/No Answer)
Call Pickup
Call Parking
Music on Hold/CRBT

Other Features

BLF
Feature Codes
Register Status
Call Logs
PBX Logs

Wi-Fi Router Features

WAN

Static IP
DHCP
PPPoE
LTE

NAT

DHCP Server

Wi-Fi

SSID
Frequency: 2.412GHz~2.484GHz
Channels: 1~14
IEEE802.11/b/g/n
Security: WPA-PSK, WPA2-PSK
AP Client MAC Address Filter
WMM (Wi-Fi Multimedia)
WPS (Wi-Fi Protected Setup): WPS-PIN, WPS-PBC

Networking Protocols

IEEE802.3(CSMA/CD), 802.3u, 802.1d/p/q/x,
802.11/b/g/n (CSMA/CA), TCP/IP, SIP, IAX, RTP,
RTCP, PPPoE, PPP, L2TP, PPTP, DHCP, ICMP, HTTP,
SNTP, SSH, etc

Firewall

MAC/IP/Port Filter
System Security: Remote Access, Ping from WAN Filter,
Block Port Scan, Block SYN Flood,
Stateful Packet Inspection (SPI)

Port Forwarding

DDNS

DDNS Support: dyndns.org, freedns.afraid.org
zoneedit.com, no-ip.com

Static Routing

Troubleshooting

Ping Test, Traceroute Test

VPN Server

L2TP/PPTP

VPN Client

L2TP/PPTP

Hardware Specifications

WAN Port

1x 10/100Base-TX Fast Ethernet, Auto MDI/MDIX

LAN Port

4x 10/100Base-TX Fast Ethernet, Auto MDI/MDIX

1 LTE Module

Telephony Port

UC52011: 1FXS+1FXO (Life-Line)

UC52002: 2FXO

USB Port

2x USB2.0

Turbo Button

Reset/WPS-PBC

RAM

DDR2 128MB

Storage

256MB Onboard Flash

Environment

Working Temperature: 0 °C ~ 40 °C

Storage Temperature: -20 °C ~ 55 °C

Humidity: 5% ~ 95% Non-Condensing

Packings

Dimension: 258mm x 250mm x 55mm

Weight/Unit: 1kg

